

PROMIG-200D

- MIG/MAG/FLUX/MMA/LIFT TIG
- 1KG/5KG wire loading
- MIG-Alum Welding
- Synergic operation

- 👍 Good effect welding, less spatter, suitable for thin plate welding.
- Ⓐ Available for $\Phi 0.6/0.8/0.9/1.0$ 1-5KG flux cored and solid wire welding.
- Ⓐ Available for $\Phi 1.0$ 1-5KG AL-Mg ER5356 welding wire.
- Ⓐ MMA available for $\Phi 1-5$ electrode rod.
- ⌚ Pre gas time, post gas time, spot time adjustment.



Applicable Materials

- Common steel plate, stainless steel, low alloy steel.



MULTIFUNCTION MIG INVERTER WELDING MACHINE		
	Unit	PROMIG-200D
Rated input voltage / frequency	V/Hz	230/50/60
Rated input power	KV	7.8
Output no-load voltage	V	60
Rated input current	A	34
MIG welding current range	A	50-200
MMA welding current range	A	20-180
TIG welding current range	A	20-180
Rated duty cycle	%	15 (40 °C) / 35 (25°C)
Efficiency	η	85%
Power factor	$\text{Cos}\phi$	0.75
Post gas time	s	0.2
Recommended welding thickness	mm	0.8-8
Insulation class		H
Protection class	IP	IP215

